



Trane ATF DEX III

TRANE ATF DEX III is formulated with premium base stocks and advanced additive technology to meet the challenging demands for automatic gears and power steering systems. It is a superior quality transmission fluid that ensures smooth power transmission while maximizing protection of components against wear and oxidation.

Sizes: 5L, 1L

Recommended for: Automatic transmissions in passenger cars and trucks- Automatic and hydrostatic transmissions in heavy duty vehicles, on and off-highway Power steering systems in cars and trucks except where other fluid types are specified. Can be used with American, European, Japanese and Korean vehicles

Benefits: Offers greater friction stability to help maintain consistently smooth shift performance in both high and low temperature. Provides Excellent protection against rust, corrosion, wear and high-temperature breakdown leading to longer transmission life. Improves thermal stability, oxidation resistance and sludge control. Improves cleanliness of transmission systems

Specifications: GM DEX IIIIG/H, GM DEX IID/E, ALLISON C-4, Caterpillar TO-2

Technical Information:

| No. | TEST ITEMS | UNIT | STANDARD TEST METHOD | SPEC. |
|-----|--------------------|------|-------------------------|---------------|
| 1 | COLOR | - | VISUAL | RED |
| 2 | DENSITY @ 15 °C | kg/L | ASTM D 4250 | 0.830 – 0.870 |
| 3 | DENSITY @ 30 °C | kg/L | ASTM D 4250 | 0.820 – 0.860 |
| 4 | FLASH POINT | °C | ASTM D 92 | 175 MIN. |
| 5 | VISCOSITY @ 40 °C | cSt | ASTM D 445 | REPORT |
| 6 | VISCOSITY @ 100 °C | cSt | ASTM D 445 | 7.0 – 7.7 |
| 7 | VISCOSITY INDEX | - | ASTM D 2270 | 150 MIN. |
| 8 | POUR POINT | °C | ASTM D 6749 | -40 MAX. |