



Trane Formula Max ECO

Trane Formula Max ECO is an advanced high performance Fully-synthetic engine oil specially designed for superior power and engine protection for eco cars. Trane Formula Max ECO is especially engineered for Eco car modern gasoline engines using specially selected Fully-synthetic base oils to give your engine

- Fuel economy with ILSAC GF-6 standard
- Deposit and wear protection
- Extended the oil drain interval
- Well balanced torque capabilities and anti-shudder durability

Suitable for Use: All Eco car with Gasoline engines

Sizes: 3L, 1L

Specifications:

SAE	0W-20
API	SP
ILSAC	GF-6

Technical Information:

No.	TEST ITEMS	UNIT	STANDARD TEST METHOD	SPEC.
				TRANE FORMULA MAX SAE 0W-20 API SP
1	DENSITY @ 15 °C	kg/L	ASTM D 4250	0.824 – 0.864
2	DENSITY @ 30 °C	kg/L	ASTM D 4250	0.815 – 0.855
3	FLASH POINT	°C	ASTM D 92	200 MIN.
4	VISCOSITY @ 40 °C	cSt	ASTM D 445	REPORT
5	VISCOSITY @ 100 °C	cSt	ASTM D 445	6.9 – 9.3
6	VISCOSITY INDEX	-	ASTM D 2270	160 MIN.
7	TOTAL BASE NUMBER	mgKOH/g	ASTM D 2896	5.0 – 9.3
8	POUR POINT	°C	ASTM D 6749	- 35 MAX.
9	CCS VISCOSITY @ -35 °C	mPa.s	ASTM D 5293	6,000 MAX.
10	CCS VISCOSITY @ -30 °C	mPa.s	ASTM D 5293	-