



Trane Formula CNG

A high-quality multi-grade engine oil specially designed for superior protection of CNG/LPG engines with superior cleaning power keeping your engine running smoother longer.

- Superior protection against high operating temperature of CNG/LPG engines
- Superior engine wear and corrosion protection, prolonging the life of the engine
- Superior cleaning power, helps to stop dirt and sludge build-up
- Superior protection against oxidation, resists oil degradation prolonging the oil-change interval

Recommended for: Gasoline engines Toyota, Honda, Nissan, Isuzu, Mitsubishi, Mercedes Benz, VW, BMW, Ford, Chevrolet, GM

Sizes: 5L

Specifications:

SAE	15W-40	20W-50
API	SJ	SJ

Technical Information:

No.	ST ITEMS	UNIT	STANDARD TEST METHOD TEST METHOD	SPEC.	SPEC.
				TRANE FORMULA CNG	TRANE FORMULA CNG
				SAE 15W-40 API SJ	SAE 20W-50 API SJ
1	DENSITY @ 15 °C	kg/L	ASTM D 4250	0.849 – 0.889	0.855 – 0.895
2	DENSITY @ 30 °C	kg/L	ASTM D 4250	0.840 – 0.880	0.845 – 0.885
3	FLASH POINT	°C	ASTM D 92	200 MIN.	200 MIN.
4	VISCOSITY @ 40 °C	cSt	ASTM D 445	REPORT	REPORT
5	VISCOSITY @ 100 °C	cSt	ASTM D 445	12.5 – 16.3	16.3 – 21.9
6	VISCOSITY INDEX	-	ASTM D 2270	125 MIN.	120 MIN.
7	TOTAL BASE NUMBER	mgKOH/g	ASTM D 2896	4.0 – 7.4	4.0 – 7.4
8	POUR POINT	°C	ASTM D 6749	- 20 MAX.	- 15 MAX.
9	CCS VISCOSITY @ -20 °C	mPa.s	ASTM D 5293	7,000 MAX.	-
10	CCS VISCOSITY @ -15 °C	mPa.s	ASTM D 5293	-	9,500 MAX.