



Trane Super Tractor THF (Transmission Hydraulic Fluid)

SAE 10W-30

A specialized agricultural transmission fluid that can be used with hydraulics, wet brakes and clutches. It can be used with agricultural tractors including ones requiring UDT Oil. Using especially selected base oils and additives Trane Super Tractor THF

- Protects tractors with specialized anti-wear, anti-corrosion, anti-foam and anti-oxidation, leading to lower downtime and longer life for your tractor.
- Provides smoother operation of tractors, by eliminating brake noise and transmission 'slip' using a specialized friction modifier.
- Is suitable with 10W-30 tractor transmission oil.
- Can be used with agricultural tractors such as Daedong, Kubota, Massey Ferguson, Case New Holland and John Deere.

Sizes: 18L, 6L

Suitable for: UDT; API: GL-4 Ford: M2C134, M2C36(A-C); Massey Ferguson: CMS M1143, M1135, M1145, M1110, M1127(A&B), M115; Case New Holland: MAT 3525 and 3526; John Deere: J20C, J20D, J20(A&B), J14, J21A; Allison: C-4, C-3; Caterpillar: T0-2 Deutz/Steiger: Hydr Trans Fluid; Denison: HF-0, HF-1, HF-2; Versatile: Gear & Hydr Trans Fluid; ZF: TE ML 03E and 05E; Volvo: Wet Brakes WB101

Technical Information:

No.	TEST ITEMS	UNIT	STANDARD	SPEC.
			TEST METHOD	
1	DENSITY @ 15 °C	kg/L	ASTM D 4250	0.851 – 0.891
2	DENSITY @ 30 °C	kg/L	ASTM D 4250	0.841 – 0.881
3	FLASH POINT	°C	ASTM D 92	200 MIN.
4	VISCOSITY @ 40 °C	cSt	ASTM D 445	REPORT
5	VISCOSITY @ 100 °C	cSt	ASTM D 445	9.3 – 12.5
6	VISCOSITY INDEX	–	ASTM D 2270	135 MIN.
7	TOTAL BASE NUMBER	mgKOH/g	ASTM D 2896	6 – 11
8	CCS VISCOSITY @ -25 °C	mPa.s	ASTM D 5293	7,000 MAX.