



## Trane T7884 Superior Axle Oil

### SAE 30

High performance multi-purpose transmission and axle oil for farm tractors

- Formulated specifically for heavy duty applications that includes extreme loading at very high temperatures, for an extended period of time
- Extremely effective protection against rust and corrosion
- Best use with: Trans-axle, clutch, wet brakes and hydraulic systems

**Sizes: 200L, 18L, 5L**

**Compatible with:** Ford M2C134A/B/C/D, M2C36 A/B/C, M2C86 A/B/C; Massey Ferguson: CMS M1143, M1135, M1145, M1110, M1127(A&B), M115; Case New Holland: MAT 3525 and 3526; John Deere: J20C, J20D, J20 A/B, J14, J21A, J27(30); Allison: C-4, C-3; Caterpillar T0-2; Deutz/Steiger Hydr Trans Fluid; Denison: HF-0, HF-1, HF-2; Versatile: Gear & Hydr Trans Fluid; ZF TE ML 03E and 05E; Volvo Wet Brakes WB101

### Technical Information:

No.	TEST ITEMS	UNIT	STANDARD TEST METHOD	SPEC.
1	DENSITY @ 15 °C	kg/L	ASTM D 4250	0.860 – 0.920
2	DENSITY @ 30 °C	kg/L	ASTM D 4250	0.850 – 0.910
3	FLASH POINT	°C	ASTM D 92	200 MIN.
4	VISCOSITY @ 40 °C	cSt	ASTM D 445	REPORT
5	VISCOSITY @ 100 °C	cSt	ASTM D 445	10.0 – 12.0
6	VISCOSITY INDEX	-	ASTM D 2270	95 MIN.
7	TOTAL BASE NUMBER	mgKOH/g	ASTM D 2896	6 – 11