



## Trane TM Turbo Plus

An exclusive motor oil blender from high quality base oils for modern passenger cars with multi-valve technology and for turbo charged gasoline engines.

- Advanced friction reduction technology for improved fuel efficiency
- To keeps engines cleaner to give improved performance and reduced exhaust pollution
- With excellent low temperature fluidity, it therefore circulates faster for instantaneous protection
- To prevents oxidative decomposition
- To increases power and saves energy for both severe service of stop and go as well as long-distance driving.

**Sizes: 5L, 1L**

### Specifications:

<b>SAE</b>	<b>20W-50</b>
<b>API</b>	<b>SL</b>

### Technical Information:

No.	TEST ITEMS	UNIT	STANDARD TEST METHOD	SPEC.
1	DENSITY @ 15 °C	kg/L	ASTM D 4250	0.855 – 0.895
2	DENSITY @ 30 °C	kg/L	ASTM D 4250	0.845 – 0.885
3	FLASH POINT	°C	ASTM D 92	200 MIN.
4	VISCOSITY @ 40 °C	cSt	ASTM D 445	REPORT
5	VISCOSITY @ 100 °C	cSt	ASTM D 445	16.3 – 21.9
6	VISCOSITY INDEX	-	ASTM D 2270	120 MIN.
7	TOTAL BASE NUMBER	mgKOH/g	ASTM D 2896	4.4 – 8.2
8	POUR POINT	°C	ASTM D 6749	- 15 MAX.
9	CCS VISCOSITY @ -15 °C	mPa.s	ASTM D 5293	9,500 MAX.